

# SAFELIFT®

PILLAR LIFT FOR INDOOR USE

## The New SD30 Stockpicker



### SPECIFICATION Safelift SD30

Size of the working platform .....	0.64 x 0.525 m
Total load on the lift .....	Max 180 kg
Total number of people .....	Max 1
Working height .....	4.95 m
Height of working platform .....	2.95 m
Basket lifting time (2,95 m) .....	16 s
Weight .....	370 kg
Total width .....	0.76 m
Total height .....	1.725 m
Total length .....	1.48 m
Driving speed lowered .....	4 km/h
Driving driving speed raised .....	2 km/h
Power source .....	2 pcs 75 Ah (C20)
	12 V batteries, maintenance-free
Line voltage .....	24 V
Battery charger .....	230 V, 50 Hz / 60 Hz
Lifting system .....	Single maneuvered hydraulic cylinder
Wheels .....	Diameter 200 mm, polyurethane coating, leaves no marks
Parking brakes .....	Automatic
Height of the platform's railing .....	1.1 m
Height of skirting board .....	0.15 m

#### LIFTING TABLE

Lifting table width .....	0.65 m
Lifting table length .....	0.44 m
Lifting table lowest height .....	0.66 m
Lifting table elevated .....	1.49 m
Lifting table stroke .....	0.83 m
Max load on lifting table .....	50 kg
Table lifting time (no load) .....	7,8 s
Table lifting time (load 50 kg) .....	11,5 s

Safelift's pillar lifts are approved in accordance with SS-EN-280

